

# DESCRIPTION LOGICS

Matthias Knorr and Pascal Hitzler

Readers: Franz Baader and Ian Horrocks

## 1 INTRODUCTION

One of the key objectives of research in Artificial Intelligence (AI) from its very beginning is the ability to represent information on a domain of interest in a compact way and, at the same time, to derive implicit information from this representation. This field in AI research is known as Knowledge Representation and Reasoning (KRR).

Description Logics (DLs) [Baader *et al.*, 2007a; Baader *et al.*, 2007b; Calvanese *et al.*, 2001; Hitzler *et al.*, 2010] emerged within KRR research from early network-based approaches, by building on their structured/taxonomic organization of a terminology of a domain of interest, but equipping it with a well-understood logic-based semantics. In fact, concepts (classes of objects) can be interpreted as unary predicates and roles (properties linking such classes) as binary predicates, and complex expressions can be built using logic-based constructors in an inductive way.

This formal underpinning proves very useful when developing inference services in Description Logics, all the more so, as it turns out that the full expressive power of first-order logic is often not required. Rather, a decidable fragment of it usually suffices, which paves the way for efficient reasoning procedures tailored to the particular language, i.e., to the necessary complex constructors, and to the concrete KRR application in mind.

Overall, the research in Description Logics and the development of KRR systems that build on DLs follow a number of important principles that distinguish the area from others in KRR research.

First, as already pointed out, the terms in the knowledge base are organized in a taxonomic, ontological way and the semantics based on first-order logics strictly adheres to the so-called open world assumption, in which inferences can only be drawn based on the content explicitly present in the knowledge base. This makes DLs particularly suitable for applications where these properties are beneficial or even required, such as modeling ontologies in the Semantic Web (cf. the corresponding chapter in this volume).

Second, as first introduced in [Brachman and Levesque, 1984], a crucial idea pursued in DL research is the trade-off between the expressive power of the language

(given the provided complex constructors) and the computational complexity of reasoning in that language. In this sense, one has to balance the admitted complex constructors for an application domain w.r.t. what is expressible and how fast inferences can be obtained. One should note here, that the aim is always to obtain a balance in which reasoning tasks are at least decidable, (independently of the concrete computational complexity), unlike other KRR formalisms that may trade decidability for more expressive power.

A third principle is the close connection between theory and practice. This is witnessed throughout the history of DLs by the mutual direct impact theoretical research and implementations (driven by actual applications, such as in natural language processing, database management, medical informatics, and software engineering to name but a few) had on each other.

Illustrating these principles, in this chapter we give an overview of Description Logics as a KRR formalism, pointing out its historic roots (Sect. 2), its syntax and semantics (Sect. 3), and algorithmic aspects (Sect. 4). We also discuss recent developments in DLs (Sect. 5) before we conclude (Sect. 6). Note that the material presented here is not meant to be exhaustive. More details can be found in [Baader *et al.*, 2007a; Baader *et al.*, 2007b; Calvanese *et al.*, 2001; Hitzler *et al.*, 2010]. In particular the DL Handbook [Baader *et al.*, 2007a] offers a very detailed account on all aspects of theory, implementation, and application of Description Logics. Furthermore, the chapter *Logics for the Semantic Web* (in this volume) discusses Description Logics in the context of the Semantic Web field, which is its currently most prominent application area.

## 2 HISTORIC ROOTS

Knowledge Representation and Reasoning as a field became considerably popular in the early 1970s and a large variety of different approaches emerged, whose underlying motivations and rationales differed substantially. Among these proposals, logic-based formalisms stem from the idea that a formalization in first-order predicate logic is most suitable due to its generality and highly expressive language. That, however, also means that reasoning, i.e., the computation of logical deductions, is in general not decidable, and also usually considerably less efficient than reasoning in a language that is tailored to the requirements of the application in mind (see, e.g., [Tsarkov *et al.*, 2004] for a more recent such comparison).

At the same time, a variety of non-logic-based formalisms were introduced. Common to them is that they were obtained by observing human behavior on resolving certain tasks or by performing cognitive experiments, and then creating formal representations that model the observations and emulate intelligent behavior. Though based on concrete observations, it was then expected that such systems would be applicable in general also to other problem domains. Unlike the logic-based approaches, knowledge representation and reasoning was achieved in a rather ad-hoc manner driven by the specific needs of an application and therefore potentially quite different from one application to the other.

One such early formalism is rule-based expert systems, such as MYCIN that, with around 450 IF-THEN rules, was able to diagnose blood infections in a similar manner as some experts and better than junior doctors (see [Russell and Norvig, 2010], also for other systems similar in spirit). These systems were, however, criticized for their lack of structure in the represented information (see, e.g., [Lehmann, 1992a]), in the sense that neither the system nor the non-expert human reader had any way to distinguish whether the encoded information was meaningful or not, so the entire search space had to be considered when reasoning, and consequently the re-use of expert systems for other purposes was rather difficult.

So-called network-based structures seemed to offer a solution for providing the (expert) knowledge in a more structured way. Network-based structures [Lehmann, 1992a; Lehmann, 1992b] themselves also represent a variety of approaches, the first being semantic networks [Quillian, 1967], in which a model of human memory is created by transferring information from a dictionary into a network of elements and their interconnections. Another prominent approach are frame systems [Minsky, 1981], in which frames serve as prototypes and relationships between such frames are expressible. Despite their differences, common to these early KRR formalisms is the objective to model sets of classes and the relations between these classes in a structured, taxonomic way.

However, the lack of formal semantics for these network-based structures meant that structured information could still be ambiguous and was therefore cause for considerable criticism [Brachman, 1977; Hayes, 1977; Hayes, 1979; Woods, 1975]. For example, a relation between two classes of individuals could mean that either there is some relation between the individuals of these classes, or that the relation is true for all individuals of these related classes, or even that the relation only holds (by default) as long as no knowledge to the contrary is explicitly available (see also [Brachman, 1983; Palomki and Kangassalo, 2012]). The consequence of this ambiguity is that many early systems building on network-based structures behave differently despite appearing to be almost identical.

In [Hayes, 1979], it was realized that a formal semantics could be provided for frames, basically by relying on first-order predicate logic: sets of individuals can be represented by unary predicates, and relations between such sets can be represented by binary predicates. One may wonder now whether this would not result simply in a logic-based formalism as described before including its disadvantages. As it turns out, network-based structures do not require the full expressiveness of first-order logic [Brachman and Levesque, 1985]. It suffices to use fragments of it, and the varying features in those network-based structures can then be represented by different (Boolean) constructors resulting in different fragments of first-order logic. As a consequence, it was recognized that reasoning in such structure-based representations could be achieved by specialized reasoners without relying on full first-order theorem provers. In addition to that, it was discovered that there is a trade-off between the expressive power of the language resulting from the inductive combination of the admitted language constructors and the computational properties of that language [Brachman and Levesque, 1984]. This also introduced the

idea of studying computational properties in terms of computational complexity to the area of DLs, and mapping out the computational complexity of different DL languages became one of the driving forces in DL research.

The first system based on such a formal semantics was KL-ONE [Brachman and Schmolze, 1985], which is based on structured inheritance networks [Brachman, 1977; Brachman, 1978]. As pointed out in [Nardi and Brachman, 2007], KL-ONE introduced many of the key notions used in Description Logics, for example, the notions of concepts and roles and the relation between them; “value restriction” and “number restriction” as new ideas that changed the use of roles when defining concepts; and the reasoning tasks of subsumption and classification (see Sect. 3 for explanations on these terms). It also paved the way towards the later distinction between TBox and ABox and provided a first example of the close connection between theory and practice in Description Logics. Moreover, KL-ONE triggered the appearance of so-called hybrid systems, such as KRYPTON [Brachman *et al.*, 1983], that combined an expressive logic- or rule-based reasoner for the ABox with a taxonomic reasoner for the TBox, and the examination and evaluation of KL-ONE and similar systems then would be the starting point for description logic systems that will be briefly described in Sect. 4.<sup>1</sup>

### 3 SYNTAX AND SEMANTICS

Traditionally speaking, a description logic is a decidable fragment of first-order predicate logic,<sup>2</sup> where decidability is obtained by disallowing function symbols and by suitably restricting the use of quantifiers. We will formally introduce the description logic  $\mathcal{ALC}$  (from *Attributive Logic with Complement*), which is usually considered to be the most *basic* description logic. We will also discuss some prominent extensions and fragments of  $\mathcal{ALC}$ . While this is only a very brief introduction, we refer the reader to [Baader *et al.*, 2007a; Baader *et al.*, 2007b; Hitzler *et al.*, 2010] for further details.

Let  $N_C$ ,  $N_R$ , and  $N_I$  be countably infinite sets of *concept names*, *role names*, and *individual names*, respectively. Concept names are also called *atomic concepts* or *atomic classes*. *Complex concepts* (in short, *concepts*) can now be formed according to the grammar

$$C ::= \top \mid \perp \mid A \mid \neg C \mid C \sqcap D \mid C \sqcup D \mid \exists R.C \mid \forall R.C,$$

where  $A \in N_C$  is an atomic concept,  $R \in N_R$  is a role, and  $C, D$  are complex concepts.  $\top$  is called the *top concept*, while  $\perp$  is called the *bottom concept*. A *general inclusion axiom (GCI)* is a statement of the form  $C \sqsubseteq D$ , where  $C$  and  $D$  are concepts. A *TBox* is a finite set of general inclusion axioms. An *ABox* is a

<sup>1</sup>More details on these DL systems and its predecessors can be found in the chapter on Description Logic Systems in the DL Handbook [Möller and Haarslev, 2007].

<sup>2</sup>However, see Sect. 5 for pointers to recent developments, which sometimes incorporate alternative semantics.

$\top$	$true$
$\perp$	$false$
$A$	$A(x)$
$\neg C$	$\neg C(x)$
$C \sqcap D$	$C(x) \wedge D(x)$
$C \sqcup D$	$C(x) \vee D(x)$
$\exists R.C$	$\exists y(R(x, y) \wedge D(y))$
$\forall R.C$	$\forall y(R(x, y) \rightarrow D(y))$
$C \sqsubseteq D$	$\forall x(C(x) \rightarrow D(x))$
$C(a)$	$C(a)$
$R(a, b)$	$R(a, b)$

Table 1. Translating description logic axioms into first-order predicate logic.

finite set of *concept assertion axioms* and *role assertion axioms*. The former are of the form  $C(a)$ , where  $C$  is a concept and  $a \in N_I$ , and the latter are of the form  $R(a, b)$ , where  $a, b \in N_I$  and  $R \in N_R$ . An  $\mathcal{ALC}$  knowledge base is a union of an ABox and a TBox.

In terms of first-order predicate logic, individuals are constants, concepts are unary predicates, and roles are binary predicates. In fact, every axiom can be translated directly into first-order predicate logic as indicated in Table 1. Of course, this translation has to be applied recursively, with suitable variable renamings.  $\mathcal{ALC}$  indeed inherits its model-theoretic semantics from first-order predicate logic by means of this translation.

With the semantics in place, a number of standard inference problems can be defined. Given an  $\mathcal{ALC}$  knowledge base  $\mathcal{K}$ ,  $\mathcal{K}$  is called *consistent* if it has a model. A concept  $C$  is *satisfiable* w.r.t.  $\mathcal{K}$  if there exists a model  $\mathcal{I}$  of  $\mathcal{K}$  with  $C^{\mathcal{I}} \neq \emptyset$ , in which case we call  $\mathcal{I}$  a *model of  $C$*  w.r.t.  $\mathcal{K}$ . Concept  $C$  is *subsumed by* concept  $D$  w.r.t.  $\mathcal{K}$ , written  $C \sqsubseteq_{\mathcal{K}} D$ , if  $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$  holds for all models  $\mathcal{I}$  of  $\mathcal{K}$ . Two concepts,  $C$  and  $D$  are *equivalent* w.r.t.  $\mathcal{K}$ , written  $C \equiv_{\mathcal{K}} D$ , if  $C$  is subsumed by  $D$  and vice-versa, and *disjoint* w.r.t.  $\mathcal{K}$  if  $C^{\mathcal{I}} \cap D^{\mathcal{I}} = \emptyset$  for every model  $\mathcal{I}$  of  $\mathcal{K}$ . Also, an individual  $a$  is an *instance of a concept  $C$*  w.r.t.  $\mathcal{K}$ , written  $\mathcal{K} \models C(a)$ , if  $a^{\mathcal{I}} \in C^{\mathcal{I}}$  holds for all models  $\mathcal{I}$  of  $\mathcal{K}$ . Likewise, a pair of individuals  $(a, b)$  is an *instance of a role  $r$*  w.r.t.  $\mathcal{K}$ , written  $\mathcal{K} \models r(a, b)$ , if  $(a^{\mathcal{I}}, b^{\mathcal{I}}) \in r^{\mathcal{I}}$  holds for all models  $\mathcal{I}$  of  $\mathcal{K}$ .

The definition of these reasoning tasks carries over to other DLs. Depending on the constructors available in a concrete DL, reasoning tasks can be reduced to each other, which means that quite often only one of those tasks has to be considered when developing inference engines. This applies for example to  $\mathcal{ALC}$  [Baader and Nutt, 2007], and it was shown that reasoning in  $\mathcal{ALC}$  is decidable [Schmidt-Schauß and Smolka, 1991], namely when establishing that concept satisfiability in  $\mathcal{ALC}$  is PSpace-hard for acyclic TBoxes, i.e., where GCIs do not form cycles, and later also ExpTime-complete in general [Schild, 1991; Donini and Massacci, 2000]. More details on complexity and related algorithms follow in Sect. 4.

$\leq nR.C$	$\mathcal{Q}$	max card.	$\bigwedge_{i=1}^{n+1} (R(x, y_i) \wedge C(y_i)) \rightarrow \bigvee_{i,j} y_i = y_j$
$\geq nR.C$	$\mathcal{Q}$	min card.	$\exists_{i=1}^n y_i (\bigwedge_i (R(x, y_i) \wedge C(y_i) \wedge \bigwedge_{j=1}^n y_i \neq y_j))$
$\{a\}$	$\mathcal{O}$	nominal	$x = a$
$R_1 \sqsubseteq R_2$	$\mathcal{H}$	role incl.	$R_1(x, y) \rightarrow R_2(x, y)$
$R_1 \circ \dots \circ R_n \sqsubseteq R$	$\mathcal{R}$	role chain	$(\bigwedge_{i=1}^n R_i(x_i, x_{i+1})) \rightarrow R(x_1, x_{n+1})$
$R_1^- \sqsubseteq R_2$	$\mathcal{I}$	inverse	$R_1(y, x) \rightarrow R_2(x, y)$

Table 2. More description logic constructs (left column), where  $R_i$  and  $R$  are roles,  $C$  is a class,  $a$  is an individual, and  $n$  is a non-negative integer. The second column gives a letter which is used to identify the construct in the commonly used description logic naming convention. In addition, the letter  $\mathcal{S}$  is used as an abbreviation for  $\mathcal{ALCH}$  with transitivity axioms of the form  $R \circ R \sqsubseteq R$ . The letter  $\mathcal{N}$  is the restriction of  $\mathcal{Q}$  to the case where  $C = \top$ .  $\mathcal{N}$  and  $\mathcal{Q}$  are also called *number restrictions*. The last column gives a translation into first-order predicate logic. Role chains are also sometimes called *complex role inclusion axioms*.

Further reasoning tasks that are commonly not of the same computational complexity can be obtained as variations of the previous ones. *Classification* requires to compute subsumptions between all concept names in the knowledge base. *Instance retrieval* focuses on the finding of instances of a given concept, while in the *realization problem*, we are searching for the most specific concept  $C$  such that  $\mathcal{K} \models C(a)$  for a given individual  $a$ . Other non-standard reasoning tasks are also listed as follows because of their potential interest for applications. Among them are *least common subsumer* [Baader *et al.*, 1999b; Küsters and Molitor, 2001], *matching* [Baader *et al.*, 1999a; Baader and Küsters, 2000] and *approximation and difference* [Brandt *et al.*, 2002]. Also of increasing importance are *explanations* for entailed information [Horridge *et al.*, 2008] also considered under *axiom pinpointing* [Kalyanpur *et al.*, 2005; Meyer *et al.*, 2006; Schlobach *et al.*, 2007; Baader and Peñaloza, 2010] and *conjunctive query answering* [Glimm *et al.*, 2008; Eiter *et al.*, 2009; Calvanese *et al.*, 2013a].

Additional constructs have been introduced for extending  $\mathcal{ALC}$  while retaining decidability. We give some of the most important ones in Table 2. In some cases, additional global syntactic restrictions have to be enforced to retain decidability.

Description logics which contain  $\mathcal{ALC}$  are very expressive but of high computational complexities (see Section 4). Description logics of comparatively low computational complexity (e.g., PTime) have also been introduced more recently, e.g. the logic  $\mathcal{EL}^{++}$ , which essentially supports only class conjunction ( $\sqcap$ ), the top concept  $\top$ , existential quantification ( $\exists R.C$ ), nominals, and role chains [Baader *et al.*, 2005].

An example for a description logic knowledge base is given in Figure 1. It describes the formal definition of a so-called ontology design pattern [Gangemi, 2005] for the notion of *trajectory*. The key idea behind the pattern is that a

$$\begin{aligned}
\text{Fix} &\sqsubseteq \exists \text{atTime}.\text{TemporalThing} \sqcap \exists \text{hasLocation}.\text{Position} \\
&\quad \sqcap \exists \text{hasFix}^-.\text{SemanticTrajectory} & (1) \\
\text{Segment} &\sqsubseteq \exists \text{startsFrom}.\text{Fix} \sqcap \exists \text{endsAt}.\text{Fix} & (2) \\
\top &\sqsubseteq \leq 1 \text{startsFrom}.\top & (3) \\
\top &\sqsubseteq \leq 1 \text{endsAt}.\top & (4) \\
\text{Segment} &\sqsubseteq \exists \text{hasSegment}^-.\text{SemanticTrajectory} & (5) \\
\text{startsFrom}^- \circ \text{endsAt} &\sqsubseteq \text{hasNext} & (6) \\
\text{hasNext} &\sqsubseteq \text{hasSuccessor} & (7) \\
\text{hasSuccessor} \circ \text{hasSuccessor} &\sqsubseteq \text{hasSuccessor} & (8) \\
\text{hasNext}^- &\sqsubseteq \text{hasPrevious} & (9) \\
\text{hasSuccessor}^- &\sqsubseteq \text{hasPredecessor} & (10) \\
\text{Fix} \sqcap \neg \exists \text{endsAt}.\text{Segment} &\sqsubseteq \text{StartingFix} & (11) \\
\text{Fix} \sqcap \neg \exists \text{startsFrom}.\text{Segment} &\sqsubseteq \text{EndingFix} & (12) \\
\text{Segment} \sqcap \exists \text{startsFrom}.\text{StartingFix} &\sqsubseteq \text{StartingSegment} & (13) \\
\text{Segment} \sqcap \exists \text{endsAt}.\text{EndingFix} &\sqsubseteq \text{EndingSegment} & (14) \\
\text{SemanticTrajectory} &\sqsubseteq \exists \text{hasSegment}.\text{Segment} & (15) \\
\text{hasSegment} \circ \text{startsFrom} &\sqsubseteq \text{hasFix} & (16) \\
\text{hasSegment} \circ \text{endsAt} &\sqsubseteq \text{hasFix} & (17) \\
\exists \text{hasSegment}.\text{Segment} &\sqsubseteq \text{SemanticTrajectory} & (18) \\
\exists \text{hasSegment}^-.\text{SemanticTrajectory} &\sqsubseteq \text{Segment} & (19) \\
\exists \text{hasFix}.\text{Segment} &\sqsubseteq \text{SemanticTrajectory} & (20) \\
\exists \text{hasFix}^-.\text{SemanticTrajectory} &\sqsubseteq \text{Fix} & (21)
\end{aligned}$$

Figure 1. Example of a *SRLN* knowledge base. It encodes a so-called *ontology design pattern* for the notion of *trajectory*. The example is taken from [Hu *et al.*, 2013].

trajectory consists of a sequence of segments, each of which has a start point and an end point—these points (together with temporal information) are called *fixes* of the segment. Axiom (1) indeed states that each fix has a location and carries temporal information (both of which are not further specified in this pattern). Furthermore, a fix is always a fix of some trajectory. Axiom (2) states that each segment starts from a fix and ends at a fix. The cardinality statements in axioms (3) and (4) state then that these two roles are *functional* in the sense that they represent binary predicates which are in fact functions. Axiom (5) states that every segment is indeed a segment of some trajectory. Axiom (6) uses role chains

to ensure that the role *hasNext* connects each fix in a trajectory directly to the next fix in the trajectory. Axioms (11) and (12) identify the first and last fix of a trajectory, while (13) and (14) identify the first and last segment of a trajectory. The remaining axioms further declare relationships between the concepts and roles, please refer to [Hu *et al.*, 2013] for further information about this pattern and the design rationales underlying it. The example can be expressed in the description logic *SRIN*: Axioms (2), (11) to (15), (18) and (20) are in *ALC*, role hierarchies ( $\mathcal{H}$ ) are used, e.g., in (7) and also transitivity is used in (8) –  $\mathcal{S}$  stands for *ALCH* plus transitivity. Role chains ( $\mathcal{R}$ ) are used, e.g., in (17), as well as cardinalities ( $\mathcal{N}$ ) for the functionality statements in (3) and (4), and several occurrences of inverse roles ( $\mathcal{I}$ ).

#### 4 ALGORITHMIC ASPECTS

In the following, we discuss algorithmic advances, the systems in which these are applied, and point out important results in computational complexity [Papadimitriou, 1994], thus drawing an arc from the first still limited DL systems in the early 1990s to the systems of today ranging from highly expressive general purpose DL reasoners to specialized highly efficient reasoners tailored to particular DLs.

In general, many of the first DL systems employ so-called structural subsumption algorithms, in which two descriptions are normalized and then their structure is compared recursively [Nebel, 1990a; Borgida and Patel-Schneider, 1994]. These algorithms are in general efficient (polynomial) for a restricted language but incomplete for more expressive DLs in the sense that not all possible inferences can be derived, and different systems adopt different positions within that scale. Namely, CLASSIC [Brachman *et al.*, 1991] permits only a limited set of constructors such that the computation is efficient and complete, while other approaches, such as LOOM [MacGregor and Bates, 1987; MacGregor, 1991] and BACK [Nebel and von Luck, 1988; Peltason, 1991], are incomplete but allow for a more expressive language. Further investigations revealed that the source of incompleteness in such systems are certain combinations of constructors in the language and that a slight increase in the expressiveness could turn reasoning intractable [Brachman and Levesque, 1985; Nebel, 1990b]. Additionally, all these systems employ rule-based and/or closed-world reasoning services (mainly on the ABox) which adds further expressiveness to the system, but causes problems since it deviates from the formal semantics due to the additions being rather ad-hoc.

Trying to overcome the limitations of these early DL systems led to the development of sound and complete algorithms for more expressive DLs and subsequently to new systems, such as KRIS [Baader and Hollunder, 1991] and CRACK [Bresciani *et al.*, 1995], that were less efficient but expressive and complete. The basic idea behind these new tableau-based algorithms [Schmidt-Schauß and Smolka, 1991; Donini *et al.*, 1991; Hollunder *et al.*, 1990] is trying to find a proof for the unsatisfiability of a concept in a constructive way. If the proof fails, then a canonical model representing a counterexample is obtained. Other reasoning tasks can be achieved



by reducing them into (un)satisfiability of a concept, which is always possible for the languages based on  $\mathcal{ALC}$  in such systems. Initially, the high worst-case complexity (ExpTime in general for  $\mathcal{ALC}$  alone) was considered problematic [Buchheit *et al.*, 1993], but empirical analysis revealed that the combinations of constructors leading to this high complexity are rarely occurring [Nebel, 1990b] and with some optimizations, the performance of a DL system could be considerably improved on average [Baader *et al.*, 1992]. Due to their generality, these new systems also turned out to be useful for comparing and benchmarking other systems [Baader *et al.*, 1992; Heinsohn *et al.*, 1992].

In general, tableau-based algorithms became the dominating approach in DL research for a number of reasons. Namely, the approach is rather flexible, i.e., a variety of languages can be covered by simply adapting the considered tableau expansion rules [Hollunder *et al.*, 1990], but also, if necessary, adopting more advanced mechanisms to ensure termination [Baader, 1991; Buchheit *et al.*, 1993]. It also turned out that, for several DL languages, the worst-case complexity of the algorithm is not worse than the complexity of deciding satisfiability for the logic [Hollunder *et al.*, 1990], making tableaux also a widely used tool in complexity analysis.

At the same time of the appearance of these first tableau-based systems, an alternative for devising algorithms and complexity analysis was introduced by establishing relations to other logical formalisms. For example, it can easily be seen from the translation of DLs to first-order predicate logic in Section 3, that  $\mathcal{ALC}$  falls within  $\mathcal{L}^2$  [Borgida, 1996], the two-variable fragment of first-order predicate logic, whose decidability was already shown in [Mortimer, 1975]. Not all of the additional constructors shown in Table 2 can be expressed in  $\mathcal{L}^2$ , but number restrictions can be expressed in  $\mathcal{C}^2$ , i.e.,  $\mathcal{L}^2$  extended by counting quantifiers, that is also decidable [Grädel *et al.*, 1997; Pacholski *et al.*, 1997]. However, algorithms building on this correspondence are in general not optimal, i.e., of higher complexity than necessary.

This differs for the relation between multi-modal logic and DLs [Schild, 1991] essentially obtained by viewing  $\exists R$  and  $\forall R$  as modalities. In fact,  $\mathcal{ALC}$  is a variant of the propositional multi-modal logic  $\mathbf{K}$ , and  $\mathcal{ALC}$  with transitive closure of roles [Baader, 1991] matches Propositional Dynamic Logic (PDL). This not only yielded the precise complexity of so-called  $\mathcal{ALC}_{trans}$  (ExpTime-complete [Fischer and Ladner, 1979]), but was also used in subsequent years to transfer known decidability results from modal logics to DLs [Schild, 1994; De Giacomo and Lenzerini, 1994a; De Giacomo and Lenzerini, 1994b; De Giacomo and Lenzerini, 1996]. Additionally, there exists a strong similarity between algorithms for deciding satisfiability in PDL and the tableau-based algorithms in DLs.

As requested by applications and driven by the just mentioned correspondence and results on tableau-based algorithms for more expressive DLs [Horrocks and Sattler, 1999; Horrocks *et al.*, 2000], the next generation of tableau-based DL systems emerged at the end of the 1990s, namely FACT [Horrocks, 1998], RACE [Haarslev and Möller, 1999], and DLP [Patel-Schneider, 1999]. These reasoners

employ considerably more expressive DL languages than before, but the use of sophisticated optimization techniques [Horrocks, 2007] ensures that these reasoners are usable in practice. Continuous further improvements, incorporating and optimizing more and more expressive features, in particular driven by the W3C standard OWL for the Semantic Web, led to highly expressive general purpose DL reasoners based on tableau algorithms incorporating DL languages whose worst-case is N2ExpTime-complete, such as FACT++ [Tsarkov and Horrocks, 2006], Pellet [Sirin *et al.*, 2007], RACER [Haarslev *et al.*, 2012] or Konclude [Steigmiller *et al.*, 2013].

In addition, more recently a number of approaches have been developed that explore alternative algorithms commonly focusing on a restricted language and aiming at more efficient reasoning. Among them is KAON2 [Motik and Sattler, 2006], which is based on ordered resolution as a means of translating *SHIQ* DL knowledge bases into disjunctive Datalog. Datalog-based reasoning has also been applied to more restricted DL languages, e.g., for DLP [Grosz *et al.*, 2003], the Horn fragment of DLs, and for  $\mathcal{EL}^{++}$  [Krötzsch, 2010]. Hermit [Motik *et al.*, 2009] builds on a combination of hypertableau and hyperresolution for *SHOIQ*<sup>+</sup>. Another approach is based on type elimination [Rudolph *et al.*, 2008a; Rudolph *et al.*, 2008b; Rudolph *et al.*, 2012] for *SHIQ*<sub>s</sub> extended with DL-safe rules by basically transforming the TBox into ordered binary decision diagrams and then to disjunctive datalog. A further line of investigation follows so-called consequence-based approaches, such as CEL [Baader *et al.*, 2006] for  $\mathcal{EL}^{++}$ , CB [Kazakov, 2009] for Horn-*SHIQ*, ConDOR [Simancik *et al.*, 2011] for *ALCH*, and ELK [Kazakov *et al.*, 2011] again for  $\mathcal{EL}^{++}$ , that classify the entire ontology in a bottom-up-like fashion achieving considerable better performance than general tableau-based algorithms.

It can be expected, that further research and new requirements from applications will push the limits of current DL systems even further. The ORE workshop [Gonçalves *et al.*, 2013] may be a good indicator for novel tendencies of DL systems, including currently among others the idea of modular reasoners, as well as reasoners for mobile devices with potentially limited resources.

## 5 RECENT DEVELOPMENTS

We briefly discuss some of the recent research developments regarding Description Logics, and give some key pointers to the literature. Our list is by no means exhaustive; an excellent way to understand the state of the art is to peruse the proceedings of the annual Description Logic Workshop<sup>3</sup> and to follow central Semantic Web outlets, such as the International Semantic Web Conference (ISWC), the Journal of Web Semantics (Elsevier), or the Semantic Web journal (IOS Press).

One of the major trends which started in the mid-2000s was to look at tractable (i.e., polynomial time complexity) Description Logics. Obvious important can-

---

<sup>3</sup>See <http://dl.kr.org/workshops/>.

didates are certain Horn fragments of Description Logics [Groszof *et al.*, 2003; Krötzsch *et al.*, 2008; Krötzsch *et al.*, 2013], but a major stepping stone was the discovery of  $\mathcal{EL}^{++}$  [Baader *et al.*, 2005], which does allow tractable standard reasoning tasks, essentially, by excluding the constructors  $\neg$ ,  $\sqcup$ , and  $\forall$ , and its application in the life sciences [Baader *et al.*, 2006]. At the same time, the DL-Lite family of Description Logics emerged [Calvanese *et al.*, 2007], that focuses on answering queries, basically by translating a conjunctive query by means of the TBox into an SQL query which can be processed using data base technology. This has gained further momentum recently with Ontology-based Data Access (ObDA) [Calvanese *et al.*, 2011; Calvanese *et al.*, 2013b; Kharlamov *et al.*, 2013], i.e., utilizing an ontology to facilitate data access by providing views and queries solely based on the language of the ontology. The importance of such tractable languages is further emphasized by the fact that they were included in the latest revision of the Web Ontology Language (OWL) standard by the World Wide Web Consortium (W3C) [Motik *et al.*, 2012; Hitzler *et al.*, 2012].

Rather classical KRR topics make their reappearance in the context of Description Logics, usually driven by the need to enhance expressivity. These include, e.g., fuzzy and probabilistic logics [Straccia, 2001; Bobillo and Straccia, 2009; Lukasiewicz and Straccia, 2009; Borgwardt and Peñaloza, 2012; Borgwardt and Peñaloza, 2013; Klinov and Parsia, 2013], temporal logics [Lutz, 2001; Sturm and Wolter, 2002; Artale *et al.*, 2013], and inconsistency handling, either through bugfixing [Huang *et al.*, 2005; Schlobach *et al.*, 2007] or through paraconsistency [Maier *et al.*, 2013]. Novel is the emphasis on decidability and on complexity issues. In particular the latter serve as a type of a-priori assessment of efficient implementability, although typical complexities are very high (see Section 4).

Important are also the relationships to other established reasoning paradigms, in particular the relation to rule-based approaches, see, e.g., [Groszof *et al.*, 2003; Horrocks *et al.*, 2004; Horrocks *et al.*, 2005; Krötzsch *et al.*, 2013; Krötzsch *et al.*, 2008; Krötzsch *et al.*, 2011; Krisnadhi *et al.*, 2011] and also the chapter on *Logics for the Semantic Web* in this volume. It was also argued very early that aspects of the closed world assumption would be required for some application contexts (see, e.g., [Grimm and Hitzler, 2008]), and so non-monotonic extensions of description logics have been created, mostly based on established approaches in the KRR field [Baader and Hollunder, 1995; Donini *et al.*, 1998; Donini *et al.*, 2002; Bonatti *et al.*, 2009; Sengupta *et al.*, 2011], and of course this has led to a combined study of rules and non-monotonicity in relation to DLs, see, e.g., [Eiter *et al.*, 2008; Motik and Rosati, 2010; Knorr *et al.*, 2011; Krisnadhi *et al.*, 2011; Knorr *et al.*, 2012] and the references contained therein.

Concrete domains [Baader and Hanschke, 1991], i.e., the enhanced use of data types, are also considered important for modeling and have drawn renewed attention recently [Lutz, 2004; Lutz *et al.*, 2005; Lutz and Milicic, 2007]. Other investigations are driven by Semantic Web-related use cases, in the wake of the adoption of Description Logics for the W3C Web Ontology Language OWL [McGuinness and van Harmelen, 2004; Hitzler *et al.*, 2012], e.g., distributed knowledge bases

[Borgida and Serafini, 2003], justifications for reasoning results [Horridge *et al.*, 2008; Horridge *et al.*, 2013], or enhancing efficiency by massive parallelization [Schlicht and Stuckenschmidt, 2010; Mutharaju *et al.*, 2013].

## 6 CONCLUSIONS

We have introduced Description Logics and described their historic roots. We also discussed algorithmic aspects from a historic perspective and considered recent research developments.

Description Logics can be traced back to network-based structures and frames. Once they became established, their development was distinguished from previous approaches to KRR by a focus on complexity and decidability. In the wake of the Semantic Web [Hitzler *et al.*, 2010], and in particular due to their adoption as one of the main Semantic Web standards [McGuinness and van Harmelen, 2004; Hitzler *et al.*, 2012]. Research on theoretical and practical aspects of Description Logics is still going strong, and its development in the near and intermediate future will likely depend on further developments related to Semantic Web technologies.<sup>4</sup>

## ACKNOWLEDGEMENTS

We would like to thank our readers Franz Baader and Ian Horrocks for their comments that helped to improve this chapter. Pascal Hitzler acknowledges support by the National Science Foundation under award 1017225 "III: Small: TROn – Tractable Reasoning with Ontologies." Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation. Matthias Knorr acknowledges support by FCT funded project ERRO – Efficient Reasoning with Rules and Ontologies (PTDC/EIA-CCO/121823/2010) and also by FCT grant SFRH/BPD/86970/2012.

## BIBLIOGRAPHY

- [Artale *et al.*, 2013] Alessandro Artale, Roman Kontchakov, Frank Wolter, and Michael Zakharyashev. Temporal Description Logic for Ontology-Based Data Access. In Francesca Rossi, editor, *IJCAI 2013, Proceedings of the 23rd International Joint Conference on Artificial Intelligence, Beijing, China, August 3-9, 2013*, pages 711–717. IJCAI/AAAI, 2013.
- [Baader and Hanschke, 1991] Franz Baader and Philipp Hanschke. A scheme for integrating concrete domains into concept languages. In John Mylopoulos and Raymond Reiter, editors, *Proceedings of the 12th International Joint Conference on Artificial Intelligence, Sydney, Australia, August 24-30, 1991*, pages 452–457. Morgan Kaufmann, 1991.
- [Baader and Hollunder, 1991] Franz Baader and Bernhard Hollunder. *KRIS: Knowledge Representation and Inference System*. *SIGART Bull.*, 2(3):8–14, 1991.
- [Baader and Hollunder, 1995] F. Baader and B. Hollunder. Embedding Defaults into Terminological Representation Systems. *J. Autom. Reasoning*, 14:149–180, 1995.

---

<sup>4</sup>See the chapter on Logics for the Semantic Web, in this volume.

- [Baader and Küsters, 2000] Franz Baader and Ralf Küsters. Matching Concept Descriptions with Existential Restrictions. In Anthony G. Cohn, Fausto Giunchiglia, and Bart Selman, editors, *KR 2000, Principles of Knowledge Representation and Reasoning Proceedings of the Seventh International Conference, Breckenridge, Colorado, USA, April 11-15, 2000*, pages 261–272. Morgan Kaufmann, 2000.
- [Baader and Nutt, 2007] Franz Baader and Werner Nutt. Basic Description Logics. In Franz Baader, Diego Calvanese, Deborah L. McGuinness, Daniele Nardi, and Peter F. Patel-Schneider, editors, *The Description Logic Handbook: Theory, Implementation, and Applications*, pages 43–95. Cambridge University Press, 2007.
- [Baader and Peñaloza, 2010] Franz Baader and Rafael Peñaloza. Axiom Pinpointing in General Tableaux. *J. Log. Comput.*, 20(1):5–34, 2010.
- [Baader et al., 1992] Franz Baader, Bernhard Hollunder, Bernhard Nebel, Hans-Jürgen Proflich, and Enrico Franconi. An Empirical Analysis of Optimization Techniques for Terminological Representation Systems, or Making KRIS Get a Move On. In Bernhard Nebel, Charles Rich, and William R. Swartout, editors, *Proceedings of the 3rd International Conference on Principles of Knowledge Representation and Reasoning (KR'92). Cambridge, MA, October 25-29, 1992*, pages 270–281. Morgan Kaufmann, 1992.
- [Baader et al., 1999a] Franz Baader, Ralf Küsters, Alexander Borgida, and Deborah L. McGuinness. Matching in Description Logics. *J. Log. Comput.*, 9(3):411–447, 1999.
- [Baader et al., 1999b] Franz Baader, Ralf Küsters, and Ralf Molitor. Computing Least Common Subsumers in Description Logics with Existential Restrictions. In Thomas Dean, editor, *Proceedings of the Sixteenth International Joint Conference on Artificial Intelligence, IJCAI 99, Stockholm, Sweden, July 31 - August 6, 1999. 2 Volumes, 1450 pages*, pages 96–103. Morgan Kaufmann, 1999.
- [Baader et al., 2005] Franz Baader, Sebastian Brandt, and Carsten Lutz. Pushing the  $\mathcal{EL}$  Envelope. In Leslie Pack Kaelbling and Alessandro Saffiotti, editors, *IJCAI-05, Proceedings of the Nineteenth International Joint Conference on Artificial Intelligence, Edinburgh, Scotland, UK, July 30-August 5, 2005*, pages 364–369. Professional Book Center, 2005.
- [Baader et al., 2006] Franz Baader, Carsten Lutz, and Boontawe Sontisrivaraporn. CEL—A Polynomial-time Reasoner for Life Science Ontologies. In Ulrich Furbach and Natarajan Shankar, editors, *Automated Reasoning, Third International Joint Conference, IJCAR 2006, Seattle, WA, USA, August 17-20, 2006, Proceedings*, volume 4130 of *Lecture Notes in Artificial Intelligence*, pages 287–291. Springer-Verlag, 2006.
- [Baader et al., 2007a] Franz Baader, Diego Calvanese, Deborah L. McGuinness, Daniele Nardi, and Peter F. Patel-Schneider, editors. *The Description Logic Handbook: Theory, Implementation, and Applications*. Cambridge University Press, 2nd edition, 2007.
- [Baader et al., 2007b] Franz Baader, Ian Horrocks, and Ulrike Sattler. Description Logics. In Frank van Harmelen, Vladimir Lifschitz, and Bruce Porter, editors, *Handbook of Knowledge Representation*. Elsevier, 2007.
- [Baader, 1991] Franz Baader. Augmenting Concept Languages by Transitive Closure of Roles: An Alternative to Terminological Cycles. In John Mylopoulos and Raymond Reiter, editors, *Proceedings of the 12th International Joint Conference on Artificial Intelligence. Sydney, Australia, August 24-30, 1991*, pages 446–451. Morgan Kaufmann, 1991.
- [Bobillo and Straccia, 2009] Fernando Bobillo and Umberto Straccia. Fuzzy description logics with general t-norms and datatypes. *Fuzzy Sets and Systems*, 160(23):3382–3402, 2009.
- [Bonatti et al., 2009] Piero A. Bonatti, Carsten Lutz, and Frank Wolter. The Complexity of Circumscription in Description Logic. *J. Artif. Intell. Res. (JAIR)*, 35:717–773, 2009.
- [Borgida and Patel-Schneider, 1994] Alexander Borgida and Peter F. Patel-Schneider. A Semantics and Complete Algorithm for Subsumption in the CLASSIC Description Logic. *J. Artif. Intell. Res. (JAIR)*, 1:277–308, 1994.
- [Borgida and Serafini, 2003] Alexander Borgida and Luciano Serafini. Distributed Description Logics: Assimilating Information from Peer Sources. *Journal on Data Semantics*, 1:153–184, 2003.
- [Borgida, 1996] Alexander Borgida. On the Relative Expressiveness of Description Logics and Predicate Logics. *Artif. Intell.*, 82(1-2):353–367, 1996.
- [Borgwardt and Peñaloza, 2012] Stefan Borgwardt and Rafael Peñaloza. Undecidability of fuzzy description logics. In Gerhard Brewka, Thomas Eiter, and Sheila A. McIlraith, editors, *Principles of Knowledge Representation and Reasoning: Proceedings of the Thirteenth International Conference, KR 2012, Rome, Italy, June 10-14, 2012*. AAAI Press, 2012.

- [Borgwardt and Peñaloza, 2013] Stefan Borgwardt and Rafael Peñaloza. The complexity of lattice-based fuzzy description logics. *J. Data Semantics*, 2(1):1–19, 2013.
- [Brachman and Levesque, 1984] Ronald J. Brachman and Hector J. Levesque. The Tractability of Subsumption in Frame-Based Description Languages. In Ronald J. Brachman, editor, *Proceedings of the National Conference on Artificial Intelligence. Austin, TX, August 6-10, 1984*, pages 34–37. AAAI Press, 1984.
- [Brachman and Levesque, 1985] Ronald J. Brachman and Hector J. Levesque, editors. *Readings in Knowledge Representation*. Morgan Kaufman, Los Altos, 1985.
- [Brachman and Schmolze, 1985] Ronald J. Brachman and James G. Schmolze. An overview of the KL-ONE knowledge representation system. *Cognitive Science*, 9(2):171–216, 1985.
- [Brachman et al., 1983] Ronald J. Brachman, Richard Fikes, and Hector J. Levesque. Krypton: A Functional Approach to Knowledge Representation. *IEEE Computer*, 16(10):67–73, 1983.
- [Brachman et al., 1991] Ronald J. Brachman, Deborah L. McGuinness, Peter F. Patel-Schneider, Lori A. Resnick, and Alexander Borgida. Living with CLASSIC: When and how to use a KL-ONE-like language. In John F. Sowa, editor, *Principles of Semantic Networks*, pages 401–456. Morgan Kaufman, Los Altos, 1991.
- [Brachman, 1977] Ronald J. Brachman. What’s in a Concept: Structural Foundations for Semantic Networks. *International Journal of Man-Machine Studies*, 9(2):127–152, 1977.
- [Brachman, 1978] Ronald J. Brachman. Structured inheritance networks. In *Research in Natural Language Understanding*, Quarterly Progress Report No. 1, BBN Report No. 3742, pages 36–78. Bolt, Beranek and Newman Inc., Cambridge, Mass., 1978.
- [Brachman, 1983] Ronald J. Brachman. What IS-A Is and Isn’t: An Analysis of Taxonomic Links in Semantic Networks. *IEEE Computer*, 16(10):30–36, 1983.
- [Brandt et al., 2002] Sebastian Brandt, Ralf Küsters, and Anni-Yasmin Turhan. Approximation and Difference in Description Logics. In Dieter Fensel, Fausto Giunchiglia, Deborah L. McGuinness, and Mary-Anne Williams, editors, *Proceedings of the Eight International Conference on Principles and Knowledge Representation and Reasoning (KR-02), Toulouse, France, April 22-25, 2002*, pages 203–214. Morgan Kaufmann, 2002.
- [Bresciani et al., 1995] Paolo Bresciani, Enrico Franconi, and Sergio Tessaris. Implementing and Testing Expressive Description Logics: Preliminary Report. In *Proc. of the 1995 Description Logic Workshop (DL’95)*, pages 131–139, 1995.
- [Buchheit et al., 1993] Martin Buchheit, Francesco M. Donini, and Andrea Schaerf. Decidable Reasoning in Terminological Knowledge Representation Systems. *J. Artif. Intell. Res. (JAIR)*, 1:109–138, 1993.
- [Calvanese et al., 2001] Diego Calvanese, Giuseppe De Giacomo, Maurizio Lenzerini, and Daniele Nardi. Reasoning in Expressive Description Logics. In John Alan Robinson and Andrei Voronkov, editors, *Handbook of Automated Reasoning*, pages 1581–1634. Elsevier and MIT Press, 2001.
- [Calvanese et al., 2007] Diego Calvanese, Giuseppe De Giacomo, Domenico Lembo, Maurizio Lenzerini, and Riccardo Rosati. Tractable Reasoning and Efficient Query Answering in Description Logics: The *DL-Lite* Family. *J. Autom. Reasoning*, 39(3):385–429, 2007.
- [Calvanese et al., 2011] Diego Calvanese, Giuseppe De Giacomo, Domenico Lembo, Maurizio Lenzerini, Antonella Poggi, Mariano Rodriguez-Muro, Riccardo Rosati, Marco Ruzzi, and Domenico Fabio Savo. The MASTRO system for ontology-based data access. *Semantic Web*, 2(1):43–53, 2011.
- [Calvanese et al., 2013a] Diego Calvanese, Giuseppe De Giacomo, Domenico Lembo, Maurizio Lenzerini, and Riccardo Rosati. Data complexity of query answering in description logics. *Artif. Intell.*, 195:335–360, 2013.
- [Calvanese et al., 2013b] Diego Calvanese, Martin Giese, Peter Haase, Ian Horrocks, Thomas Hubauer, Yannis E. Ioannidis, Ernesto Jiménez-Ruiz, Evgeny Kharlamov, Herald Killapi, Johan W. Klüwer, Manolis Koubarakis, Steffen Lamparter, Ralf Möller, Christian Neuenstadt, T. Nordtveit, Özgür L. Özçep, Mariano Rodriguez-Muro, Mikhail Roshchin, Domenico Fabio Savo, Michael Schmidt, Ahmet Soylu, Arild Waaler, and Dmitriy Zheleznyakov. Optique: OBDA Solution for Big Data. In Philipp Cimiano, Miriam Fernández, Vanessa Lopez, Stefan Schlobach, and Johanna Völker, editors, *The Semantic Web: ESWC 2013 Satellite Events – ESWC 2013 Satellite Events, Montpellier, France, May 26-30, 2013, Revised Selected Papers*, volume 7955 of *Lecture Notes in Computer Science*, pages 293–295. Springer, 2013.

- [De Giacomo and Lenzerini, 1994a] Giuseppe De Giacomo and Maurizio Lenzerini. Boosting the Correspondence between Description Logics and Propositional Dynamic Logics. In Barbara Hayes-Roth and Richard E. Korf, editors, *Proceedings of the 12th National Conference on Artificial Intelligence, Seattle, WA, USA, July 31 - August 4, 1994, Volume 1*, pages 205–212. AAAI Press / The MIT Press, 1994.
- [De Giacomo and Lenzerini, 1994b] Giuseppe De Giacomo and Maurizio Lenzerini. Concept Language with Number Restrictions and Fixpoints, and its Relationship with  $\mu$ -calculus. In Anthony G. Cohn, editor, *Proceedings of the Eleventh European Conference on Artificial Intelligence, Amsterdam, The Netherlands, August 8-12*, pages 411–415. John Wiley and Sons, 1994.
- [De Giacomo and Lenzerini, 1996] Giuseppe De Giacomo and Maurizio Lenzerini. TBox and ABox Reasoning in Expressive Description Logics. In Luigia Carlucci Aiello, Jon Doyle, and Stuart C. Shapiro, editors, *Proceedings of the Fifth International Conference on Principles of Knowledge Representation and Reasoning (KR'96), Cambridge, Massachusetts, USA, November 5-8, 1996*, pages 316–327. Morgan Kaufmann, 1996.
- [Donini and Massacci, 2000] Francesco M. Donini and Fabio Massacci. ExpTime tableaux for *ALC*. *Artif. Intell.*, 124(1):87–138, 2000.
- [Donini et al., 1991] Francesco M. Donini, Maurizio Lenzerini, Daniele Nardi, and Werner Nutt. The Complexity of Concept Languages. In James F. Allen, Richard Fikes, and Erik Sandewall, editors, *Proceedings of the 2nd International Conference on Principles of Knowledge Representation and Reasoning (KR'91), Cambridge, MA, USA, April 22-25, 1991*, pages 151–162. Morgan Kaufmann, 1991.
- [Donini et al., 1998] Francesco M. Donini, Maurizio Lenzerini, Daniele Nardi, Andrea Schaerf, and Werner Nutt. An epistemic operator for description logics. *Artif. Intell.*, 100(1-2):225–274, 1998.
- [Donini et al., 2002] Francesco M. Donini, Daniele Nardi, and Riccardo Rosati. Description logics of minimal knowledge and negation as failure. *ACM Trans. Comput. Log.*, 3(2):177–225, 2002.
- [Eiter et al., 2008] Thomas Eiter, Giovambattista Ianni, Thomas Lukasiewicz, Roman Schindlauer, and Hans Tompits. Combining answer set programming with description logics for the Semantic Web. *Artif. Intell.*, 172:1495–1539, 2008.
- [Eiter et al., 2009] Thomas Eiter, Carsten Lutz, Magdalena Ortiz, and Mantas Simkus. Query Answering in Description Logics with Transitive Roles. In Craig Boutilier, editor, *IJCAI 2009, Proceedings of the 21st International Joint Conference on Artificial Intelligence, Pasadena, California, USA, July 11-17, 2009*, pages 759–764, 2009.
- [Fischer and Ladner, 1979] Michael J. Fischer and Richard E. Ladner. Propositional Dynamic Logic of Regular Programs. *J. Comput. Syst. Sci.*, 18(2):194–211, 1979.
- [Gangemi, 2005] Aldo Gangemi. Ontology Design Patterns for Semantic Web Content. In Yolanda Gil, Enrico Motta, V. Richard Benjamins, and Mark A. Musen, editors, *The Semantic Web - ISWC 2005, 4th International Semantic Web Conference, ISWC 2005, Galway, Ireland, November 6-10, 2005, Proceedings*, volume 3729 of *Lecture Notes in Computer Science*, pages 262–276. Springer, 2005.
- [Glimm et al., 2008] Birte Glimm, Carsten Lutz, Ian Horrocks, and Ulrike Sattler. Conjunctive Query Answering for the Description Logic *SHTQ*. *J. Artif. Intell. Res. (JAIR)*, 31:157–204, 2008.
- [Gonçalves et al., 2013] Rafael S. Gonçalves, Samantha Bail, Ernesto Jiménez-Ruiz, Nicolas Matentzoglou, Bijan Parsia, Birte Glimm, and Yevgeny Kazakov. OWL Reasoner Evaluation (ORE) Workshop 2013 Results: Short Report. In Samantha Bail, Birte Glimm, Rafael S. Gonçalves, Ernesto Jiménez-Ruiz, Yevgeny Kazakov, Nicolas Matentzoglou, and Bijan Parsia, editors, *Informal Proceedings of the 2nd International Workshop on OWL Reasoner Evaluation (ORE-2013), Ulm, Germany, July 22, 2013*, volume 1015 of *CEUR Workshop Proceedings*, pages 1–18. CEUR-WS.org, 2013.
- [Grädel et al., 1997] Erich Grädel, Martin Otto, and Eric Rosen. Two-Variable Logic with Counting is Decidable. In *Proceedings, 12th Annual IEEE Symposium on Logic in Computer Science, Warsaw, Poland, June 29 - July 2, 1997*, pages 306–317. IEEE Computer Society, 1997.
- [Grimm and Hitzler, 2008] Stephan Grimm and Pascal Hitzler. Semantic Matchmaking of Web Resources with Local Closed-World Reasoning. *International Journal of Electronic Commerce*, 12(2):89–126, 2008.

- [Grosf *et al.*, 2003] Benjamin N. Grosf, Ian Horrocks, Raphael Volz, and Stefan Decker. Description logic programs: combining logic programs with description logic. In Gusztáv Hencsey, Bebo White, Yih-Farn Robin Chen, László Kovács, and Steve Lawrence, editors, *Proceedings of the Twelfth International World Wide Web Conference, WWW 2003, Budapest, Hungary, May 20-24, 2003*, pages 48–57. ACM, 2003.
- [Haarslev and Möller, 1999] Volker Haarslev and Ralf Möller. RACE System Description. In Patrick Lambrix, Alexander Borgida, Maurizio Lenzerini, Ralf Möller, and Peter F. Patel-Schneider, editors, *Proceedings of the 1999 International Workshop on Description Logics (DL'99), Linköping, Sweden, July 30 - August 1, 1999*, volume 22 of *CEUR Workshop Proceedings*. CEUR-WS.org, 1999.
- [Haarslev *et al.*, 2012] Volker Haarslev, Kay Hidde, Ralf Möller, and Michael Wessel. The RacerPro Knowledge Representation and Reasoning System. *Semantic Web*, 3(3):267–277, 2012.
- [Hayes, 1977] Patrick J. Hayes. In Defense of Logic. In R. Reddy, editor, *Proceedings of the 5th International Joint Conference on Artificial Intelligence. Cambridge, MA, August 1977*, pages 559–565. William Kaufmann, 1977.
- [Hayes, 1979] Patrick J. Hayes. The logic of frames. In D. Metzger, editor, *Frame conceptions and text understanding*, pages 46–61. Walter de Gruyter and Co., 1979. Republished in [Brachman and Levesque, 1985].
- [Heinsohn *et al.*, 1992] Jochen Heinsohn, Daniel Kudenko, Bernhard Nebel, and Hans-Jürgen Profitlich. An Empirical Analysis of Terminological Representation Systems. In William R. Swartout, editor, *Proceedings of the 10th National Conference on Artificial Intelligence. San Jose, CA, July 12-16, 1992*, pages 767–773. AAAI Press / The MIT Press, 1992.
- [Hitzler *et al.*, 2010] Pascal Hitzler, Markus Krötzsch, and Sebastian Rudolph. *Foundations of Semantic Web Technologies*. Chapman & Hall/CRC, 2010.
- [Hitzler *et al.*, 2012] Pascal Hitzler, Markus Krötzsch, Bijan Parsia, Peter F. Patel-Schneider, and Sebastian Rudolph, editors. *OWL 2 Web Ontology Language: Primer (Second Edition)*. W3C Recommendation 11 December 2012, 2012. Available from <http://www.w3.org/TR/owl2-primer/>.
- [Hollunder *et al.*, 1990] Bernhard Hollunder, Werner Nutt, and Manfred Schmidt-Schauß. Subsumption Algorithms for Concept Description Languages. In *9th European Conference on Artificial Intelligence, ECAI'90, Stockholm, Sweden*, pages 348–353, 1990.
- [Horridge *et al.*, 2008] Matthew Horridge, Bijan Parsia, and Ulrike Sattler. Laconic and Precise Justifications in OWL. In Amit P. Sheth, Steffen Staab, Mike Dean, Massimo Paolucci, Diana Maynard, Timothy W. Finin, and Krishnaprasad Thirunarayan, editors, *The Semantic Web - ISWC 2008, 7th International Semantic Web Conference, ISWC 2008, Karlsruhe, Germany, October 26-30, 2008. Proceedings*, volume 5318 of *Lecture Notes in Computer Science*, pages 323–338. Springer, 2008.
- [Horridge *et al.*, 2013] Matthew Horridge, Samantha Bail, Bijan Parsia, and Uli Sattler. Toward cognitive support for OWL justifications. *Knowl.-Based Syst.*, 53:66–79, 2013.
- [Horrocks and Sattler, 1999] Ian Horrocks and Ulrike Sattler. A Description Logic with Transitive and Inverse Roles and Role Hierarchies. *J. Log. Comput.*, 9(3):385–410, 1999.
- [Horrocks *et al.*, 2000] Ian Horrocks, Ulrike Sattler, and Stephan Tobies. Practical Reasoning for Very Expressive Description Logics. *Logic Journal of the IGPL*, 8(3):239–263, 2000.
- [Horrocks *et al.*, 2004] Ian Horrocks, Peter F. Patel-Schneider, Harold Boley, Said Tabet, Benjamin Grosf, and Mike Dean. *SWRL: A Semantic Web Rule Language Combining OWL and RuleML*. W3C Member Submission 21 May 2004, 2004. Available from <http://www.w3.org/Submission/SWRL/>.
- [Horrocks *et al.*, 2005] Ian Horrocks, Peter F. Patel-Schneider, Sean Bechhofer, and Dmitry Tsarkov. OWL Rules: A Proposal and Prototype Implementation. *Journal of Web Semantics*, 3(1):23–40, 2005.
- [Horrocks, 1998] Ian Horrocks. Using an Expressive Description Logic: FaCT or Fiction? In Anthony G. Cohn, Lenhart K. Schubert, and Stuart C. Shapiro, editors, *Proceedings of the Sixth International Conference on Principles of Knowledge Representation and Reasoning (KR'98), Trento, Italy, June 2-5, 1998*, pages 636–649. Morgan Kaufmann, 1998.
- [Horrocks, 2007] Ian Horrocks. Implementation and Optimization Techniques. In Franz Baader, Diego Calvanese, Deborah L. McGuinness, Daniele Nardi, and Peter F. Patel-Schneider, editors, *The Description Logic Handbook: Theory, Implementation, and Applications*, pages 306–346. Cambridge University Press, 2007.



- [Hu *et al.*, 2013] Yingjie Hu, Krzysztof Janowicz, David Carral Martínez, Simon Scheider, Werner Kuhn, Gary Berg-Cross, Pascal Hitzler, Mike Dean, and Dave Kolas. A Geo-ontology Design Pattern for Semantic Trajectories. In Thora Tenbrink, John G. Stell, Antony Galton, and Zena Wood, editors, *Spatial Information Theory - 11th International Conference, COSIT 2013, Scarborough, UK, September 2-6, 2013. Proceedings*, volume 8116 of *Lecture Notes in Computer Science*, pages 438–456. Springer, 2013.
- [Huang *et al.*, 2005] Zhisheng Huang, Frank van Harmelen, and Annette ten Teije. Reasoning with Inconsistent Ontologies. In Leslie Pack Kaelbling and Alessandro Saffiotti, editors, *IJCAI-05, Proceedings of the Nineteenth International Joint Conference on Artificial Intelligence, Edinburgh, Scotland, UK, July 30-August 5, 2005*, pages 454–459. Professional Book Center, 2005.
- [Kalyanpur *et al.*, 2005] Aditya Kalyanpur, Bijan Parsia, Evren Sirin, and James A. Hendler. Debugging unsatisfiable classes in OWL ontologies. *J. Web Sem.*, 3(4):268–293, 2005.
- [Kazakov *et al.*, 2011] Yevgeny Kazakov, Markus Krötzsch, and Frantisek Simancik. Concurrent Classification of  $\mathcal{EL}$  Ontologies. In Lora Aroyo, Chris Welty, Harith Alani, Jamie Taylor, Abraham Bernstein, Lalana Kagal, Natasha Fridman Noy, and Eva Blomqvist, editors, *The Semantic Web - ISWC 2011 - 10th International Semantic Web Conference, Bonn, Germany, October 23-27, 2011, Proceedings, Part I*, volume 7031 of *Lecture Notes in Computer Science*, pages 305–320. Springer, 2011.
- [Kazakov, 2009] Yevgeny Kazakov. Consequence-Driven Reasoning for Horn  $\mathcal{SHIQ}$  Ontologies. In Craig Boutilier, editor, *IJCAI 2009, Proceedings of the 21st International Joint Conference on Artificial Intelligence, Pasadena, California, USA, July 11-17, 2009*, pages 2040–2045, 2009.
- [Kharlamov *et al.*, 2013] Evgeny Kharlamov, Martin Giese, Ernesto Jiménez-Ruiz, Martin G. Skjæveland, Ahmet Soylu, Dmitriy Zheleznyakov, Timea Bagosi, Marco Console, Peter Haase, Ian Horrocks, Sarunas Marciuska, Christoph Pinkel, Mariano Rodriguez-Muro, Marco Ruzzi, Valerio Santarelli, Domenico Fabio Savo, Kunal Sengupta, Michael Schmidt, Evgenij Thorstensen, Johannes Trame, and Arild Waaler. Optique 1.0: Semantic Access to Big Data: The Case of Norwegian Petroleum Directorate’s FactPages. In Eva Blomqvist and Tudor Groza, editors, *Proceedings of the ISWC 2013 Posters & Demonstrations Track, Sydney, Australia, October 23, 2013*, volume 1035 of *CEUR Workshop Proceedings*, pages 65–68. CEUR-WS.org, 2013.
- [Klinov and Parsia, 2013] Pavel Klinov and Bijan Parsia. Understanding a Probabilistic Description Logic via Connections to First-Order Logic of Probability. In Fernando Bobillo, Paulo Cesar G. da Costa, Claudia d’Amato, Nicola Fanizzi, Kathryn B. Laskey, Kenneth J. Laskey, Thomas Lukasiewicz, Matthias Nickles, and Michael Pool, editors, *Uncertainty Reasoning for the Semantic Web II, International Workshops URSW 2008-2010 Held at ISWC and UniDL 2010 Held at FLoC, Revised Selected Papers*, volume 7123 of *Lecture Notes in Computer Science*, pages 41–58. Springer, 2013.
- [Knorr *et al.*, 2011] M. Knorr, J.J. Alferes, and P. Hitzler. Local Closed-World Reasoning with Description Logics under the Well-founded Semantics. *Artif. Intell.*, 175(9–10):1528–1554, 2011.
- [Knorr *et al.*, 2012] M. Knorr, P. Hitzler, and F. Maier. Reconciling OWL and non-monotonic rules for the Semantic Web. In Luc De Raedt, Christian Bessière, Didier Dubois, Patrick Doherty, Paolo Frasconi, Fredrik Heintz, and Peter J. F. Lucas, editors, *ECAI 2012, 20th European Conference on Artificial Intelligence, 27-31 August 2012, Montpellier, France*, volume 242 of *Frontiers in Artificial Intelligence and Applications*, pages 474–479. IOS Press, Amsterdam, 2012.
- [Krisnadhi *et al.*, 2011] Adila Krisnadhi, Frederick Maier, and Pascal Hitzler. OWL and Rules. In Axel Polleres, Claudia d’Amato, Marcelo Arenas, Siegfried Handschuh, Paula Kroner, Sascha Ossowski, and Peter F. Patel-Schneider, editors, *Reasoning Web. Semantic Technologies for the Web of Data - 7th International Summer School 2011, Galway, Ireland, August 23-27, 2011, Tutorial Lectures*, volume 6848 of *Lecture Notes in Computer Science*, pages 382–415. Springer, 2011.
- [Krötzsch *et al.*, 2008] Markus Krötzsch, Sebastian Rudolph, and Pascal Hitzler. Description Logic Rules. In Malik Ghallab, Constantine D. Spyropoulos, Nikos Fakotakis, and Nikolaos M. Avouris, editors, *Proceeding of the 18th European Conference on Artificial Intelligence, Patras, Greece, July 21-25, 2008*, volume 178, pages 80–84. Amsterdam, The Netherlands, 2008. IOS Press.

- [Krötzsch *et al.*, 2011] Markus Krötzsch, Frederick Maier, Adila A. Krisnadhi, and Pascal Hitzler. A Better Uncle for OWL: Nominal Schemas for Integrating Rules and Ontologies. In Sadagopan Srinivasan, Krithi Ramamritham, Arun Kumar, M. P. Ravindra, Elisa Bertino, and Ravi Kumar, editors, *Proceedings of the 20th International World Wide Web Conference, WWW2011, Hyderabad, India, March/April 2011*, pages 645–654. ACM, New York, 2011.
- [Krötzsch *et al.*, 2013] M. Krötzsch, S. Rudolph, and P. Hitzler. Complexities of Horn Description Logics. *ACM Trans. on Comput. Log.*, 14(1):2–36, 2013.
- [Krötzsch, 2010] Markus Krötzsch. Efficient Inferencing for OWL EL. In Tomi Janhunnen and Ilkka Niemelä, editors, *Logics in Artificial Intelligence - 12th European Conference, JELIA 2010, Helsinki, Finland, September 13-15, 2010. Proceedings*, volume 6341 of *Lecture Notes in Computer Science*, pages 234–246. Springer, 2010.
- [Küstners and Molitor, 2001] Ralf Küstners and Ralf Molitor. Computing Least Common Subsumers in  $\mathcal{ALN}$ . In Bernhard Nebel, editor, *Proceedings of the Seventeenth International Joint Conference on Artificial Intelligence, IJCAI 2001, Seattle, Washington, USA, August 4-10, 2001*, pages 219–224. Morgan Kaufmann, 2001.
- [Lehmann, 1992a] Fritz Lehmann. Semantic Networks. *Computers Math. Applic.*, 23(2-5):1–50, 1992.
- [Lehmann, 1992b] Fritz Lehmann. *Semantic Networks in Artificial Intelligence*. Elsevier Science Inc., New York, NY, USA, 1992.
- [Lukasiewicz and Straccia, 2009] Thomas Lukasiewicz and Umberto Straccia. Description logic programs under probabilistic uncertainty and fuzzy vagueness. *Int. J. Approx. Reasoning*, 50(6):837–853, 2009.
- [Lutz and Milicic, 2007] Carsten Lutz and Maja Milicic. A Tableau Algorithm for Description Logics with Concrete Domains and General TBoxes. *J. Autom. Reasoning*, 38(1–3):227–259, 2007.
- [Lutz *et al.*, 2005] Carsten Lutz, Carlos Areces, Ian Horrocks, and Ulrike Sattler. Keys, Nominals, and Concrete Domains. *J. Artif. Intell. Res. (JAIR)*, 23:667–726, 2005.
- [Lutz, 2001] Carsten Lutz. Interval-based Temporal Reasoning with General TBoxes. In Bernhard Nebel, editor, *Proceedings of the Seventeenth International Joint Conference on Artificial Intelligence, IJCAI 2001, Seattle, Washington, USA, August 4-10, 2001*, pages 89–96. Morgan Kaufmann, 2001.
- [Lutz, 2004] Carsten Lutz. NEXP TIME-complete description logics with concrete domains. *ACM Trans. Comput. Log.*, 5(4):669–705, 2004.
- [MacGregor and Bates, 1987] Robert MacGregor and Raymond Bates. The LOOM knowledge representation language. Technical Report ISI/RS-87-188, University of Southern California, Information Science Institute, Marina de Rey (CA, USA), 1987.
- [MacGregor, 1991] Robert MacGregor. The evolving technology of classification-based knowledge representation systems. In John Sowa, editor, *Principles of Semantic Networks*, pages 385–400. Morgan Kaufmann, Los Altos, 1991.
- [Maier *et al.*, 2013] Frederick Maier, Yue Ma, and Pascal Hitzler. Paraconsistent OWL and related logics. *Semantic Web*, 4(4):395–427, 2013.
- [McGuinness and van Harmelen, 2004] Deborah McGuinness and Frank van Harmelen. *OWL Web Ontology Language: Overview*. W3C Recommendation 10 February 2004, 2004. Available from <http://www.w3.org/TR/owl-features/>.
- [Meyer *et al.*, 2006] Thomas Andreas Meyer, Kevin Lee, Richard Booth, and Jeff Z. Pan. Finding Maximally Satisfiable Terminologies for the Description Logic  $\mathcal{ALC}$ . In *Proceedings, The Twenty-First National Conference on Artificial Intelligence and the Eighteenth Innovative Applications of Artificial Intelligence Conference, July 16-20, 2006, Boston, Massachusetts, USA*, pages 269–274. AAAI Press, 2006.
- [Minsky, 1981] Marvin Minsky. A framework for representing knowledge. In John Haugeland, editor, *Mind Design: Philosophy, Psychology, Artificial Intelligence*, pages 95–128. MIT Press, Cambridge, MA, 1981. A longer version appeared in *The Psychology of Computer Vision* (1975). Republished in [Brachman and Levesque, 1985].
- [Möller and Haarslev, 2007] Ralf Möller and Volker Haarslev. Description Logic Systems. In Franz Baader, Diego Calvanese, Deborah L. McGuinness, Daniele Nardi, and Peter F. Patel-Schneider, editors, *The Description Logic Handbook: Theory, Implementation, and Applications*, pages 282–305. Cambridge University Press, 2007.
- [Mortimer, 1975] Michael Mortimer. On languages with two variables. *Zeitschrift für Mathematische Logik und Grundlagen der Mathematik*, 21:135–140, 1975.

- [Motik and Rosati, 2010] Boris Motik and Riccardo Rosati. Reconciling Description Logics and Rules. *J. ACM*, 57(5):1–62, 2010.
- [Motik and Sattler, 2006] Boris Motik and Ulrike Sattler. A Comparison of Reasoning Techniques for Querying Large Description Logic ABoxes. In Miki Hermann and Andrei Voronkov, editors, *Logic for Programming, Artificial Intelligence, and Reasoning, 13th International Conference, LPAR 2006, Phnom Penh, Cambodia, November 13-17, 2006, Proceedings*, volume 4246 of *Lecture Notes in Computer Science*, pages 227–241. Springer, 2006.
- [Motik et al., 2009] Boris Motik, Rob Shearer, and Ian Horrocks. Hypertableau Reasoning for Description Logics. *J. Artif. Intell. Res. (JAIR)*, 36:165–228, 2009.
- [Motik et al., 2012] Boris Motik, Bernardo Cuenca Grau, Ian Horrocks, Zhe Wu, Achille Fokoue, and Carsten Lutz, editors. *OWL 2 Web Ontology Language: Profiles (Second Edition)*. W3C Recommendation 11 December 2012, 2012. Available at <http://www.w3.org/TR/owl2-profiles/>.
- [Mutharaju et al., 2013] Raghava Mutharaju, Pascal Hitzler, and Prabhaker Mateti. DistEL: A Distributed EL+ Ontology Classifier. In Thorsten Liebig and Achille Fokoue, editors, *Proceedings of the 9th International Workshop on Scalable Semantic Web Knowledge Base Systems, Sydney, Australia, October 21, 2013*, volume 1046 of *CEUR Workshop Proceedings*, pages 17–32. CEUR-WS.org, 2013.
- [Nardi and Brachman, 2007] Daniele Nardi and Ronald J. Brachman. An Introduction to Description Logics. In Franz Baader, Diego Calvanese, Deborah L. McGuinness, Daniele Nardi, and Peter F. Patel-Schneider, editors, *The Description Logic Handbook: Theory, Implementation, and Applications*, pages 1–40. Cambridge University Press, 2007.
- [Nebel and von Luck, 1988] Bernhard Nebel and Kai von Luck. Hybrid Reasoning in BACK. In *Proceedings of the 3rd International Symposium on Methodologies for Intelligent Systems (ISMIS'88)*, pages 260–269. North-Holland Publ. Co., Amsterdam, 1988.
- [Nebel, 1990a] Bernhard Nebel. *Reasoning and Revision in Hybrid Representation Systems*, volume 422 of *Lecture Notes in Computer Science*. Springer, 1990.
- [Nebel, 1990b] Bernhard Nebel. Terminological Reasoning is Inherently Intractable. *Artif. Intell.*, 43(2):235–249, 1990.
- [Pacholski et al., 1997] Leszek Pacholski, Wieslaw Szwaast, and Lidia Tendera. Complexity of Two-Variable Logic with Counting. In *Proceedings, 12th Annual IEEE Symposium on Logic in Computer Science, Warsaw, Poland, June 29 - July 2, 1997*, pages 318–327. IEEE Computer Society, 1997.
- [Palomki and Kangassalo, 2012] Jari Palomki and Hannu Kangassalo. That IS-IN Isn't IS-A: A Further Analysis of Taxonomic Links in Conceptual Modelling. In Carlos Ramirez, editor, *Advances in Knowledge Representation*. InTech, 2012. Available from: <http://www.intechopen.com/books/advances-in-knowledge-representation/that-is-in-isn-t-is-a-a-further-analysis-of-taxonomic-links-in-conceptual-modelling>.
- [Papadimitriou, 1994] Christos H. Papadimitriou. *Computational complexity*. Addison-Wesley, 1994.
- [Patel-Schneider, 1999] Peter F. Patel-Schneider. DLP. In Patrick Lambrix, Alexander Borgida, Maurizio Lenzerini, Ralf Möller, and Peter F. Patel-Schneider, editors, *Proceedings of the 1999 International Workshop on Description Logics (DL'99), Linköping, Sweden, July 30 - August 1, 1999*, volume 22 of *CEUR Workshop Proceedings*. CEUR-WS.org, 1999.
- [Peltason, 1991] Christof Peltason. The BACK System - An Overview. *SIGART Bull.*, 2(3):114–119, 1991.
- [Quillian, 1967] M. Ross Quillian. Word concepts: A theory and simulation of some basic capabilities. *Behavioral Science*, 12:410–430, 1967.
- [Rudolph et al., 2008a] Sebastian Rudolph, Markus Krötzsch, and Pascal Hitzler. Description Logic Reasoning with Decision Diagrams: Compiling *SHIQ* to Disjunctive Datalog. In Amit P. Sheth, Steffen Staab, Mike Dean, Massimo Paolucci, Diana Maynard, Timothy W. Finin, and Krishnaprasad Thirunarayan, editors, *The Semantic Web - ISWC 2008, 7th International Semantic Web Conference, ISWC 2008, Karlsruhe, Germany, October 26-30, 2008. Proceedings*, volume 5318 of *Lecture Notes in Computer Science*, pages 435–450. Springer, 2008.
- [Rudolph et al., 2008b] Sebastian Rudolph, Markus Krötzsch, and Pascal Hitzler. Terminological Reasoning in *SHIQ* with Ordered Binary Decision Diagrams. In Dieter Fox and Carla P. Gomes, editors, *Proceedings of the Twenty-Third AAAI Conference on Artificial Intelligence, AAAI 2008, Chicago, Illinois, USA, July 13-17, 2008*, pages 529–534. AAAI Press, 2008.

- [Rudolph *et al.*, 2012] Sebastian Rudolph, Markus Krötzsch, and Pascal Hitzler. Type-elimination-based reasoning for the description logic  $\mathcal{SHIQ}_b$  using decision diagrams and disjunctive Datalog. *Logical Methods in Computer Science*, 8(1), 2012.
- [Russell and Norvig, 2010] Stuart J. Russell and Peter Norvig. *Artificial Intelligence - A Modern Approach (3. internat. ed.)*. Pearson Education, 2010.
- [Schild, 1991] Klaus Schild. A Correspondence Theory for Terminological Logics: Preliminary Report. In John Mylopoulos and Raymond Reiter, editors, *Proceedings of the 12th International Joint Conference on Artificial Intelligence. Sydney, Australia, August 24-30, 1991*, pages 466–471. Morgan Kaufmann, 1991.
- [Schild, 1994] Klaus Schild. Terminological Cycles and the Propositional  $\mu$ -Calculus. In Jon Doyle, Erik Sandewall, and Pietro Torasso, editors, *Proceedings of the 4th International Conference on Principles of Knowledge Representation and Reasoning (KR'94). Bonn, Germany, May 24-27, 1994*, pages 509–520. Morgan Kaufmann, 1994.
- [Schlicht and Stuckenschmidt, 2010] Anne Schlicht and Heiner Stuckenschmidt. Peer-to-Peer Reasoning for Interlinked Ontologies. *Int. J. Semantic Computing*, 4(1):27–58, 2010.
- [Schlobach *et al.*, 2007] Stefan Schlobach, Zhisheng Huang, Ronald Cornet, and Frank van Harmelen. Debugging Incoherent Terminologies. *J. Autom. Reasoning*, 39(3):317–349, 2007.
- [Schmidt-Schauß and Smolka, 1991] Manfred Schmidt-Schauß and Gert Smolka. Attributive Concept Descriptions with Complements. *Artif. Intell.*, 48(1):1–26, 1991.
- [Sengupta *et al.*, 2011] Kunal Sengupta, Adila Alfa Krisnadhi, and Pascal Hitzler. Local Closed World Semantics: Grounded Circumscription for OWL. In Lora Aroyo, Chris Welty, Harith Alani, Jamie Taylor, Abraham Bernstein, Lalana Kagal, Natasha Fridman Noy, and Eva Blomqvist, editors, *The Semantic Web – ISWC 2011 – 10th International Semantic Web Conference, Bonn, Germany, October 23-27, 2011, Proceedings, Part I*, volume 7031 of *Lecture Notes in Computer Science*, pages 617–632. Springer, Heidelberg, 2011.
- [Simancik *et al.*, 2011] Frantisek Simancik, Yevgeny Kazakov, and Ian Horrocks. Consequence-Based Reasoning beyond Horn Ontologies. In Toby Walsh, editor, *IJCAI 2011, Proceedings of the 22nd International Joint Conference on Artificial Intelligence, Barcelona, Catalonia, Spain, July 16-22, 2011*, pages 1093–1098. IJCAI/AAAI, 2011.
- [Sirin *et al.*, 2007] Evren Sirin, Bijan Parsia, Bernardo Cuenca Grau, Aditya Kalyanpur, and Yarden Katz. Pellet: A practical OWL-DL reasoner. *Web Semantics*, 5:51–53, 2007.
- [Steigmiller *et al.*, 2013] Andreas Steigmiller, Birte Glimm, and Thorsten Liebig. Nominal Schema Absorption. In Francesca Rossi, editor, *IJCAI 2013, Proceedings of the 23rd International Joint Conference on Artificial Intelligence, Beijing, China, August 3-9, 2013*. IJCAI/AAAI, 2013.
- [Straccia, 2001] Umberto Straccia. Reasoning within Fuzzy Description Logics. *J. Artif. Intell. Res. (JAIR)*, 14:137–166, 2001.
- [Sturm and Wolter, 2002] Holger Sturm and Frank Wolter. A Tableau Calculus for Temporal Description Logic: the Expanding Domain Case. *J. Log. Comput.*, 12(5):809–838, 2002.
- [Tsarkov and Horrocks, 2006] Dmitry Tsarkov and Ian Horrocks. FaCT++ description logic reasoner: System description. In Ulrich Furbach and Natarajan Shankar, editors, *In Proceedings of the International Joint Conference on Automated Reasoning (IJCAR 2006)*, pages 292–297. Springer, 2006.
- [Tsarkov *et al.*, 2004] Dmitry Tsarkov, Alexandre Riazanov, Sean Bechhofer, and Ian Horrocks. Using Vampire to Reason with OWL. In Sheila A. McIlraith, Dimitris Plexousakis, and Frank van Harmelen, editors, *The Semantic Web – ISWC 2004: Third International Semantic Web Conference, Hiroshima, Japan, November 7-11, 2004. Proceedings*, volume 3298 of *Lecture Notes in Computer Science*, pages 471–485. Springer, 2004.
- [Woods, 1975] William A. Woods. What's in a link: Foundations for semantic networks. In Daniel G. Bobrow and Allan M. Collins, editors, *Representation and Understanding: Studies in Cognitive Science*, pages 35–82. Academic Press, 1975. Republished in [Brachman and Levesque, 1985].